

T8 LED Slim Batten Fitting

Model: OS BS 2x600mm



Specifications & Technical Data

- Housing is Fabricated From Mild Steel (*Thickness 0.3mm*)
- Finished With Powder Electrostatically
- Stove-Coated With High Reflectivity White Epoxy
- Lampholder of Polycarbonate & Bronze
- Twist-Lock Lampholder For Reliable Contact
- Pre-Connected With 105°C HR PVC Cable
- Connecting Devices of Nylon 3 Way x 2.5mm²
- Degree of Protection: **IP20**
- Type of Protection: Class 1
- Mounting Method: Surface Ceiling / Wall / Suspension


- Optional:**
- VITALITE VECK 18/T8 LED
 - 2 Hours Duration Emergency Powerpack



Model	Luminaires				Dimension - mm			Current (A)	P.F. (λ)
	No. of Lamp	Power	Beam Angle	Base	L	W	H	± 5 %	>
OS BS 2x600mm	2	2 x 8W	130°	G13	612	88	65	0.07	> 0.90

Lamp (AC Input 100-240V, 50/60Hz, Athd < 15%) (2ft)											
Brand	Code	Type	Base	Lumens (lm)	Power (W)	CCT (K)	CRI (Ra)	SDCM	Current	P.F.	Lifespan (Hrs)
TOSHIBA	T8 LEDtube PRO 600mm 8W 4000K (RLDL0282C0840G1EX1)	T8 LED	G13	1100lm	8W	4000K	≥ 80Ra	≤ 6	0.035	> 0.9	50000Hrs
TOSHIBA	T8 LEDtube PRO 600mm 8W 6500K (RLDL0282C0865G1EX1)	T8 LED	G13	1100lm	8W	6500K	≥ 80Ra	≤ 6	0.035	> 0.9	50000Hrs

Photometric Data



Flux Out: 390.8 lm		
(M)	Lux	CM
1	373	115
2	93	231
3	41	346
4	23	462
5	15	577

Height Angle: 60° Diameter