



YLI INDUSTRY SDN. BHD.

Ultimate Lighting Experience



LED A50  
(5W)

LED A55  
(7W)

LED A60  
(9W)

LED A60L  
(12W)

LED A95  
(20W)

## LED A Bulb A Series

Wide range of brightness with all 3 colour temperatures options, TOSHIBA LED A Series have been useful over the time, generation to generation. Long lasting, robust and Eyes safety LED quality with 200 degree wide beam angle.



| Product Code   | Bulb Shape | Rated Wattage (W) | Luminous Flux (lm) | Colour Temperature (K) | Voltage (V) | Efficacy (lm/W) | CRI (Ra) | Beam Angle (°) | Lifespan (Hrs) | Dimension (mm) |
|----------------|------------|-------------------|--------------------|------------------------|-------------|-----------------|----------|----------------|----------------|----------------|
| RLDAJ0530E7EX1 | A50        | 5                 | 405                | 3000                   | 180 - 240   | 81              | 80       | 200            | 15000          | D50 x H92      |
| RLDAJ0540E7EX1 | A50        | 5                 | 425                | 4000                   | 180 - 240   | 85              | 80       | 200            | 15000          | D50 x H92      |
| RLDAJ0565E7EX1 | A50        | 5                 | 450                | 6500                   | 180 - 240   | 90              | 80       | 200            | 15000          | D50 x H92      |
| RLDAJ0730E7EX1 | A55        | 7                 | 560                | 3000                   | 180 - 240   | 80              | 80       | 200            | 15000          | D55 x H104     |
| RLDAJ0740E7EX1 | A55        | 7                 | 600                | 4000                   | 180 - 240   | 86              | 80       | 200            | 15000          | D55 x H104     |
| RLDAJ0765E7EX1 | A55        | 7                 | 630                | 6500                   | 180 - 240   | 90              | 80       | 200            | 15000          | D55 x H104     |
| RLDAJ0930E7EX1 | A60        | 9                 | 730                | 3000                   | 180 - 240   | 81              | 80       | 200            | 15000          | D60 x H115     |
| RLDAJ0940E7EX1 | A60        | 9                 | 770                | 4000                   | 180 - 240   | 86              | 80       | 200            | 15000          | D60 x H115     |
| RLDAJ0965E7EX1 | A60        | 9                 | 810                | 6500                   | 180 - 240   | 90              | 80       | 200            | 15000          | D60 x H115     |
| RLDAJ1230E7EX1 | A60L       | 12                | 970                | 3000                   | 180 - 240   | 81              | 80       | 200            | 15000          | D60 x H117     |
| RLDAJ1240E7EX1 | A60L       | 12                | 1025               | 4000                   | 180 - 240   | 85              | 80       | 200            | 15000          | D60 x H117     |
| RLDAJ1265E7EX1 | A60L       | 12                | 1080               | 6500                   | 180 - 240   | 90              | 80       | 200            | 15000          | D60 x H117     |
| RLDAJ2030E7EX1 | A95        | 20                | 1620               | 3000                   | 180 - 240   | 81              | 80       | 200            | 15000          | D95 x H174     |
| RLDAJ2065E7EX1 | A95        | 20                | 1800               | 6500                   | 180 - 240   | 90              | 80       | 200            | 15000          | D95 x H174     |

Equivalent: (Compare to incandescent lamp)

5W = 35W | 7W = 50W | 9W = 60W | 12W = 80W | 20W = 110W

Operation Temperature : -20°C to +40°C

Lamp Survival Factor @ 6000Hrs = 90%

Lamp Lumen Maintenance Factor @ 6000Hrs = 86.7%